
1/16 Indicator**pH/ORP/Temp Conductivity/TDS/Salt/Temp Indicator****Features:**

1. Compact 1/16 DIN size fits into standard industry panel cutouts.
2. Microprocessor based for fast, reliable and accurate measurements.
3. Easy to calibrate by one keyboard. Degree °C/°F are switchable.
4. The large backlight LCD display pH or Conductivity and Temperature simultaneously.
5. Optional NEMA-4X gasketed lens cover fits over front bezel of controller-made of watertight corrosion resistant ABS plastic.

Specifications:

	pH	ORP	Temp	Conductivity	TDS	Salt	Temp
Range	- 2~16.00	±1000 mV	0~90.0 °C	0~2000µS 2.00~20.00 mS	0-1300 ppm 1.30~13.00 ppt	0~1000 ppm 1.00~10.00 ppt	0~90 °C
Accuracy	±0.01+1 digit	±2+1 digit	±0.2+1 digit	±2% FS			±0.2+1 digit
Resolution	0.01 pH	1 mV	0.1 °C	1 µS/0.01 mS	1 ppm/0.01 ppt	1 ppm/0.01 ppt	
Power	9V DC (AC adaptor)						
Panel cutout	1/16 DIN/1.77 x 1.77"(45 x 45 mm), Depth 4.2"(106 mm)						
Weight	70 g without NEMA-4X						

Accessories for complete kit:

1. pH, ORP electrode or Conductivity cell
2. Temperature probe
3. Standard solution
4. DC/AC adaptor



Conductivity/TDS/Salt



pH/ORP