

Model:

PAT-PP-201 pH Meter

PAT-PP-203 pH/mV/Temp Meter

PAT-PP-206 pH/mV/Temp Meter with STO/RCL & MAX/MIN

Feature:

1. Microprocessor based with splash proof housing.
2. Large LCD built into adjustable "flip-up" cover. Simultaneous display pH and Temperature.
3. Rugged design for handheld or bench top use, neckstrap for "hands-free" operation.
4. Automatic or manual temperature compensation. °C/°F switchable
5. Simple to calibrate by one keyboard for 5 points buffer, calibration value can be adjusted as needed.
6. Memory stores and recalls up to 20 points. Min/Max storage and recall. (PP- 206 only)
7. Indicate percentage of slope (PTS) after calibration.
8. Low battery and consumption indicator.
9. Auto shut off after 10 minutes of non use .



Specifications:

	PP-201	PP-203			PP-206		
	pH	pH	mV	Temp.	pH	mV	Temp.
Range:	0-14.00	0-14.00	±1999	0-100 °C	0-14.00	±1999	0-100 °C
Accuracy:	±0.01+1 digit	±0.01+1 digit	±1+1 digit	±0.2 °C+1 digit	±0.01+1 digit	±1+1 digit	±0.2 °C+1 digit
Resolution:	0.01	0.01	1	0.1 °C	0.01	1	0.1 °C
Compensation:	MTC:0-100 °C	ATC: 0-100 °C		ATC: 0-100 °C			
Battery:	9V	9V or AC Adaptor		9V or AC Adaptor			
Multi-function	None	None		Storage/Recall, Min/Max			
Calibration:	pH4.00, 7.00, 10.00						
Dimensions:	96 x 120 x 46 mm (folded)						
Weight:	260 g (with battery)						

Accessories for complete kit:

1. pH electrode.
2. Buffer solution 4 & 7.
3. Distilled water.
4. 9V Battery.
5. Instruction manual.
6. Carrying case.
7. Temperature probe(Pt 100) for PP-203 & PP-206 only.
8. Optional: AC/DC adaptor